

1 Identification of the substance/preparation and of the company/undertaking

· **Product details**

- **Trade name:** *Acryl-Lackspray 7022 / Rittal Nr: 2581.000*
- **Application of the substance / the preparation** *Color spray to touch up painted surfaces*

· **Manufacturer/Supplier:**

*Rittal GmbH & Co. KG
Auf dem Stützelberg
D-35745 Herborn (Germany)
Tel.: +49(0)2772-505-0
Fax.: +49(0)2772-505-70107
e-mail: info@rittal.de
www.rittal.de*

- **Further information obtainable from:** *Marketing Tel. +49(0)2772 / 505 - 9052*
- **Information in case of emergency:** *+ 49(0)228-19240 (24 h Hotline, german speaking)*

2 Hazards identification

· **Hazard description:**



*Xi Irritant
F Highly flammable*

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

Has a narcotizing effect.

R 11 Highly flammable.

R 36 Irritating to eyes.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

· **Chemical characterization**

- **Description:** *Mixture of substances listed below with nonhazardous additions.*

· **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2	acetone Xi, F; R 11-36-66-67	10-25%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate R 10-66-67	10-25%
CAS: 74-98-6 EINECS: 200-827-9	propane F+; R 12	10-25%
CAS: 106-97-8 EINECS: 203-448-7	butane F+; R 12	10-25%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Xi; R 10-36	2.5-10%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. Xn, Xi, N; R 10-37-51/53-65-66-67	≤ 2.5%

(Contd. on page 2)



Trade name: Acryl-Lackspray 7022 / Rittal

(Contd. of page 1)

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

* 5 Fire-fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

* 6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

* 7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 3)

Trade name: Acryl-Lackspray 7022 / Rittal

(Contd. of page 2)

· Ingredients with limit values that require monitoring at the workplace:	
67-64-1 acetone	
WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
123-86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
106-97-8 butane	
WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
108-65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles



Trade name: Acryl-Lackspray 7022 / Rittal

(Contd. of page 3)

9 Physical and chemical properties

· General Information

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44°C

· **Flash point:** 1°C (DIN 53213)

· **Ignition temperature:** 365°C (DIN 51794)

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:	1.2 Vol %
Upper:	13.0 Vol %

· **Vapour pressure at 20°C:** 8300 hPa

· **Density at 20°C:** 0.735 g/cm³ (DIN 53217)

· **Solubility in / Miscibility with water:** Not miscible or difficult to mix.

· Viscosity:

Kinematic at 20°C: 1 s (DIN 53211/4)

· **Solvent separation test:** < 3 %

· Solvent content:

Organic solvents:	79.3 %
VOC (EC)	583.4 g/l

· **Solids content (weight-%):** 20.7 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous decomposition products:** Carbon monoxide

11 Toxicological information

· Acute toxicity:

· LD/LC50 values relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

· Primary irritant effect:

- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

(Contd. on page 5)

Trade name: Acryl-Lackspray 7022 / Rittal

(Contd. of page 4)

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

15 01 04	metallic packaging
----------	--------------------

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 2 5F Gases.
- **Danger code (Kemler):** -
- **UN-Number:** 1950
- **Packaging group:** -
- **Hazard label:** 2.1
- **Description of goods:** 1950 AEROSOLS

· **Maritime transport IMDG:**



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label:** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No

(Contd. on page 6)

Trade name: Acryl-Lackspray 7022 / Rittal

(Contd. of page 5)

· **Proper shipping name:** AEROSOLS

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 2.1
 · **UN/ID Number:** 1950
 · **Label:** 2.1
 · **Packaging group:** -
 · **Proper shipping name:** AEROSOLS, flammable

15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

Xi Irritant
F Highly flammable

· **Risk phrases:**

11 Highly flammable.
36 Irritating to eyes.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

2 Keep out of the reach of children.
3 Keep in a cool place.
9 Keep container in a well-ventilated place.
16 Keep away from sources of ignition - No smoking.
23 Do not breathe fumes/aerosol.
46 If swallowed, seek medical advice immediately and show this container or label.

· **National regulations:**

· **Information about limitation of use:**

64-17-5	ethanol	5
---------	---------	---

Class	Share in %
NK	50-100

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

10 Flammable.
11 Highly flammable.
12 Extremely flammable.
36 Irritating to eyes.
37 Irritating to respiratory system.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31



Printing date 30.01.2009

Revision: 30.01.2009

Trade name: Acryl-Lackspray 7022 / Rittal

(Contd. of page 6)

- 65 *Harmful: may cause lung damage if swallowed.*
- 66 *Repeated exposure may cause skin dryness or cracking.*
- 67 *Vapours may cause drowsiness and dizziness.*

· *Department issuing MSDS: RITTAL GmbH & Co. KG*

· ** Data compared to the previous version altered.*

GB